



**NOTES:**

1. ROADWAY STRUCTURAL SECTIONS SHOWN ARE MINIMUMS. ACTUAL STRUCTURAL COMPONENT VALUES SHALL BE DETERMINED BY SOILS/TRAFFIC ANALYSES FOR "R" VALUE AND TRAFFIC INDEX (T1). IN NO CASE SHALL THE ACTUAL STRUCTURAL SECTION BE LESS THAN THE MINIMUMS SHOWN.
2. PAVEMENT CROSS-SLOPES ARE MINIMUM-MAXIMUM VALUES.
3. SIDEWALK PATTERNS AND R/W WIDTH WILL VARY WITH LOCATION. SEE STD. DRAWING ST-5 FOR "CONCRETE CURB & GUTTER AND SIDEWALK."
4. FOG SEAL SHALL BE APPLIED WHEN SPECIFIED.
5. ALL WET UTILITY SPACING MUST COMPLY WITH STATE GUIDANCE MEMO 2003-02. SEE STANDARD SPECIFICATIONS.
6. APPLY TACK COAT TO GUTTER PAN FACE PRIOR TO PAVING.



# CITY OF CLOVIS

DWG NO.  
**ST-1**

## LOCAL STREET SECTIONS AND UTILITY LOCATIONS

REF.: STD. SPECIFICATIONS  
SECTIONS 19, 26, 37,  
39, 73, APPENDIX

APPROVED BY:	NO.	REVISED	BY	APPROVALS	SCALE: NTS
CITY ENGINEER DATE: 10/22/15	---	01-13-11	BGJ	CM DRU PUD	DRAWN BY: JA
	---	11-22-11	PAA		
	---	10-27-15	CGV		
					SHEET 1 OF 1