

NOTES:

1. POSTS FOR COMBINED STREET SIGN AND OBJECT MARKER SHALL BE 12 GAUGE 2" X 2" SQUARE, GALVANIZED AND PERFORATED.
2. FOR POSTS TO BE USED IN COMBINATION WITH PEDESTRIAN PUSH BUTTON POLES, REFER TO TRAFFIC SIGNAL STD. DRAWINGS NO. TS-7 & TS-7A.
3. POST AND FLANGE FOR TYPE 2 (OM2-1H) OBJECT MARKER SHALL BE SCHED. 80 PVC, 2-1/4" O.D. MIN.
4. OBJECT MARKER SHALL BE TYPE 2, REFLECTORIZED (YELLOW REFLECTORS) CONFORMING TO CAL MUTCID OM2-1H.
5. ANCHOR W/ PENETRATOR SHALL BE 30" "ANCHOR-MATE W/ 12" SLEEVE", ULTIMATE HIGHWAY PRODUCTS, INC. MODEL 9UM 225 / 30250/12 OR APPROVED EQUAL. SEE STD. DRAWING NO. ST-15A. ANCHOR TO BE INSTALLED NO MORE THAN 2 1/2" ABOVE GRADE.
6. INSTALL 3" THICK CLASS 3 CONCRETE CAP MINIMUM 6' FROM NOSE. CERTAIN LOCATIONS MAY REQUIRE STAMPED CONCRETE.




CITY OF CLOVIS

MEDIAN ISLAND NOSE MARKER & SIGN

DWG NO.
ST-15

REF.:
STD. SPECIFICATIONS

APPROVED BY: 

CITY ENGINEER

DATE: 10/29/13

NO.	REVISED	BY
	03-26-13	BGJ
	05-29-12	PAA
	09-28-12	PAA

APPROVALS

CM 

DRU 

PUD 

SCALE: NTS

DRAWN BY: JA

SHEET 1 OF 1