

ANCHOR TO BE INSTALLED NO MORE THAN 2½" ABOVE GRADE

2-1/2" X 2-1/2" X 12 GA. @ 12" LONG SLEEVE

FILLET WELD ALL AROUND

2-1/4" X 2-1/4" X 12 GA. @ 30" LONG STEEL TUBE

CORNER BOLTS SHALL BE USED TO SECURE POST TO SLEEVE

Ø7/16" HOLES (4 SIDES)

FILLET WELD ALL AROUND

NOTE:

POST ANCHOR SHALL BE 30" ANCHOR-MATE W/12" SLEEVE, ULTIMATE HIGHWAY PRODUCTS, INC. MODEL 9UM 225/30250/12. OR APPROVED EQUAL. COMPANY ADDRESS: P.O. BOX 7 STANTON, CA 90680

EXPLODED VIEW

SIDE VIEW



CITY OF CLOVIS

DWG NO. **ST-15A**

STREET SIGN POST ANCHOR

REF.: STD. SPECIFICATIONS SECTION 84

APPROVED BY:	NO.	REVISED	BY	APPROVALS	SCALE: NTS
CITY ENGINEER		05-20-09	BGJ	 	DRAWN BY: JA
		01-14-11	BGJ		SHEET 1 OF 1
	DATE: 10/2/12	09-28-12	PAA		