



**NOTES:**

1. FORMED CURB SHALL BE CLASS 3 CONCRETE; EXTRUDED CURBS SHALL BE CLASS 2.
2. CURBS SHALL BE BROOM FINISH.
3. COMPACT MEDIAN FILL MATERIAL TO 90% UNDER SURFACES TO BE PAVED.
4. MEDIAN FILL MATERIAL MAY VARY DEPENDING ON LANDSCAPING REQUIREMENTS.
5. FILL INSIDE MEDIAN BEFORE PLACING AND/OR COMPACTING MATERIAL IN THE TRAVELED WAY.
6. FOR DIRT-ONLY MEDIAN (NO LANDSCAPING IN PROJECT) OMIT STAMPED CONCRETE WALKWAY.
7. ALL COLORED STAMPED CONCRETE SHALL BE SEALED WITH TWO COATS OF "CLEAR SEAL 400", OR APPROVED EQUAL.



# CITY OF CLOVIS

## MEDIAN ISLAND CURB DETAILS (NEW AC PAVEMENT)

DWG NO.  
**ST-25**

REF.:  
STD. SPECIFICATIONS

APPROVED BY:		NO.	REVISED	BY	APPROVALS	SCALE: NTS
CITY ENGINEER			3-26-12	PAA	CM	DRAWN BY: JA
			05-29-12	PAA	DRU	
			09-28-12	PAA	PUD	
DATE:	10/2/12					SHEET 1 OF 1