



NOTES:

1. FORMED CURB SHALL BE CLASS 3 CONCRETE; EXTRUDED CURBS SHALL BE CLASS 2.
2. CURBS SHALL BE BROOM FINISH.
3. COMPACT MEDIAN FILL MATERIAL TO 90% UNDER SURFACES TO BE PAVED.
4. MEDIAN FILL MATERIAL MAY VARY DEPENDING ON LANDSCAPING REQUIREMENTS.
5. FILL INSIDE MEDIAN BEFORE PLACING AND/OR COMPACTING MATERIAL IN THE TRAVELED WAY.
6. ALL COLORED STAMPED CONCRETE SHALL BE SEALED WITH TWO COATS OF "CLEAR SEAL 100", OR APPROVED EQUAL.



CITY OF CLOVIS
MEDIAN ISLAND CURB DETAILS
 (EXISTING AC PAVEMENT)

DWG NO.
ST-25A

REF.:
 STD. SPECIFICATIONS

APPROVED BY:	NO.	REVISED	BY	APPROVALS	SCALE: NTS	
CITY ENGINEER <i>[Signature]</i>		3-26-12	PAA	CM <i>[Signature]</i>	DRAWN BY: JA	
		05-29-12	PAA	DRU <i>[Signature]</i>		
	DATE: 6/29/17		09-28-12	PAA	PUD <i>[Signature]</i>	SHEET 1 OF 1
			06-12-17	CGV		