



**NOTES:**

1. FORMED CURB SHALL BE CLASS 3 CONCRETE; EXTRUDED CURBS SHALL BE CLASS 2.
2. CURBS SHALL BE BROOM FINISH.
3. COMPACT MEDIAN FILL MATERIAL TO 90% UNDER SURFACES TO BE PAVED.
4. MEDIAN FILL MATERIAL MAY VARY DEPENDING ON LANDSCAPING REQUIREMENTS.
5. FILL INSIDE MEDIAN BEFORE PLACING AND/OR COMPACTING MATERIAL IN THE TRAVELED WAY.
6. FOR DIRT-ONLY MEDIAN (NO LANDSCAPING IN PROJECT) OMIT STAMPED CONCRETE WALKWAY.
7. ALL COLORED STAMPED CONCRETE SHALL BE SEALED WITH TWO COATS OF "CLEAR SEAL 400", OR APPROVED EQUAL.



**CITY OF CLOVIS**  
**MEDIAN ISLAND CURB DETAILS**  
 (EXISTING AC PAVEMENT)

DWG NO.  
**ST-25A**

REF.:  
 STD. SPECIFICATIONS

APPROVED BY:	NO.	REVISED	BY	APPROVALS	SCALE: NTS
CITY ENGINEER DATE: 10/2/12		3-26-12	PAA	CM DRU PUD	DRAWN BY: JA
		05-29-12	PAA		SHEET 1 OF 1
		09-28-12	PAA		