



- NOTES:**
1. ROADWAY STRUCTURAL SECTIONS SHOWN ARE MINIMUMS. ACTUAL STRUCTURAL COMPONENT VALUES SHALL BE DETERMINED BY SOILS/TRAFFIC ANALYSES FOR "R" VALUE AND TRAFFIC INDEX (TI). IN NO CASE SHALL THE ACTUAL STRUCTURAL SECTION BE LESS THAN THE MINIMUMS SHOWN.
 2. PAVEMENT CROSS-SLOPES ARE MINIMUM-MAXIMUM VALUES.
 3. SIDEWALK PATTERNS AND R/W WIDTH WILL VARY WITH LOCATION. SEE STD. DRAWING ST-5 FOR "CONCRETE CURB & GUTTER AND SIDEWALK."
 4. FOG SEAL SHALL BE APPLIED WHEN SPECIFIED.
 5. ALL WET UTILITY SPACING MUST COMPLY WITH STATE GUIDANCE MEMO 2003-02. SEE STANDARD SPECIFICATIONS.
 6. ADDITIONAL R/W MAY BE REQUIRED FOR BICYCLE LANES AND BUS TURNOUTS.
 7. APPLY TACK COAT TO GUTTER PAN/MEDIAN CURB FACE PRIOR TO PAVING.



CITY OF CLOVIS

FOUR LANE MAJOR STREET SECTIONS AND UTILITY LOCATIONS

DWG NO.
ST-3

REF.: STD. SPECIFICATIONS SECTIONS 19, 26, 37, 39, 73, APPENDIX

APPROVED BY: *[Signature]*
CITY ENGINEER
DATE: 10/22/15

NO.	REVISED	BY
	01-13-11	BGJ
	11-22-11	PAA
	10-27-15	CGV

APPROVALS
CM *[Signature]*
DRU *[Signature]*
PUD *[Signature]*

SCALE: NTS
DRAWN BY: JA
SHEET 1 OF 1